



ABOUT US

Virgo Lubricants Trading L.L.C is a UAE based company that offers a full range of lubricants and greases for various industries, including automotive, industrial and marine applications. At Virgo we are committed to supplying high-quality lubricants that meet industry standards, and we have a team of experienced professionals who provide technical support to our customers.



OUR VISION

Become a leading trader and supplier of Lubricants and Greases by striving for excellence. Continue to reach out for greater heights through continuous improvement of product quality and service, meeting our clients' needs at all times while adhering to the latest international norms.



OUR VALUE

- Integrity
- Innovation
- Transparency
- Commitment
- Teamwork
- Customer Satisfaction

عن الشركة

فيرجو لتجارة الزيوت ش.ذ.م.م هي شركة مقرها دولة الإمارات العربية المتحدة، تقدم مجموعة كاملة من الزيوت والشحوم لمختلف الصناعات بما في ذلك السيارات والصناعة والقطاع البحري. نلتزم في فيرجو بتوريد زيوت تشحيم عالية الجودة تلي معايير الصناعة، ولدينا فريق من المحترفين ذوي الخبرة يقدم الدعم الفني لعملائنا.

رؤيتنا

أن نصبح من الشركات الرائدة في تجارة وتوريد زيوت التشحيم والشحوم من خلال السعي لتحقيق التميز، والاستمرار في الوصول إلى أعلى المستويات من خلال التحسين المستمر لجودة المنتجات والخدمات، وتلبية احتياجات العملاء في جميع الأوقات مع الالتزام بأحدث المعايير الدولية.

قيمتنا

- نزاهة
- ابتكار
- الشفافية
- التزام
- العمل بروح الفريق الواحد
- رضا العملاء



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L

GASOLINE ENGINE OILS

زيوت محركات البنزين

SAE Viscosity	K. Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40°C	100°C				
0W20	46	8.25	155	232	-39	* API SL, SM, SN
5W-20	48-55	8.5-9.3	≥150	≥200	≤ -39	* API SP
5W-30	58-66	10.0-11.0	≥150	≥200	≤ -39	* API SP
5W40	85.3	14.3	174	242	-39	* API SL, SM, SN
10W-40	95-110	13.5-14.5	≥140	≥210	≤ -30	* API SP
20W50	160	19.1	136	242	-29	* API SL, SM, SN

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L

DIESEL ENGINE OILS

زيوت محركات الديزل

SAE Viscosity	K. Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40°C	100°C				
5W30	64	10.5	153	224	-39	* API CH, CI, CJ, CK *ACEA A3/B4
5W40	103	14.9	151	238	-39	
10W40	92.5	14.3	160	242	-39	* API CH, CI, CJ, CK *ACEA A3/B4
15W40	103	14.5	145	234	-32	* API CH, CI, CJ, CK *ACEA A3/B4
20W50	155	19.1	140	248	-30	* API CH, CI, CJ, CK *ACEA A3/B4

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

GEAR OILS

زيوت التروس

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
SAE 90	161	15.5	95	230	-33	GL-4, GL-5
SAE 140	204	18.0	95	310	-12	
80W90	136	14.5	105	202	-30	
80W140	188.9	25	165	225	-38	
85W140	410	28.9	96	210	-15	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

TRACTOR FLUID

سائل الجرار

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
GL-5	69.3	10.4	136	230	-36	GL-4, GL-5

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

ATF (Automatic Transmission Fluid)

السائل ناقل حركة أوتوماتيكي

DEX Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
ATF II	28.0	5.8	160	222	-51	Dexron - 2
ATF III	38.0	7.6	175	226	-45	Dexron - 3
CVT Fluid	34.2	7.1	179	214	-51	Suitable for use where Dexron VI is required

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L

MOTORCYCLE OILS

زيوت الدراجات النارية

SAE Viscosity	K.Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	Application
	40 °C	100 °C				
4T	98.5	14.5	152	226	-40	For 4-strokes engine motorcycles. JASO MA MA2 API SN
10W40	108.1	14.6	139	236	-36	
20W50	160.5	18.8	132	248	-33	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

COMPRESSOR OILS

زيت الضاغط

API Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 32	0.860	32.0	5.5	108	230	-30	1a	*Reciprocating type compressors
ISO VG 46	0.867	46.0	7.0	109	234	-30	1a	
ISO VG 68	0.872	68.0	9.0	107	236	-27	1a	
ISO VG 32	0.860	32.0	5.5	108	230	-30	1a	*Rotary type compressors
ISO VG 46	0.867	46.0	7.0	109	234	-30	1a	
ISO VG 68	0.872	68.0	9.0	107	236	-27	1a	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

ANTIFREEZE COOLANT

سائل تبريد المحرك

Concentration (%)		Freezing Point (°C)
Water (%)	A/F (%)	
0(%)	100(%)	-20°C
70(%)	30(%)	-17°C
50(%)	50(%)	-36°C
40(%)	60(%)	-52°C
30(%)	70(%)	-18°C

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

HYDRAULIC OILS

زيوت هيدروليكية

ISO Viscosity	Density (15°C) kg/l	K. Viscosity (cSt)		VI	Flash Point °C	Demulsibility D1401	Application
		40°C	100°C				
ISO VG 32	0.870	32	5.4	95	212	15 (54°C)	*Anti-wear (AW) hydraulic oil for industrial & mobile hydraulic systems *Meets the requirements of: DIN 51524 Part 2, Denison HF-0/HF-1/HF-2, Vickers M-2950S & I-286S, Cincinnati Milacron P-68/P-69/P-70, AFNOR NF E 48-603 HM, U.S. Steel 136/127
ISO VG 46	0.875	46	6.7	95	226	15 (54°C)	
ISO VG 68	0.880	68	8.5	95	234	20 (54°C)	
ISO VG 100	0.885	100	11.1	95	242	10 (84°C)	
ISO VG 150	0.889	150	14.6	95	258	5 (84°C)	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L

BRAKE FLUID

زيت الفرامل

Type	K. Viscosity (cSt)		Corrosion test 120 Hrs.	ERPB	pH	Wet ERBP	Application
	40°C	100°C					
DOT 3	1300	2.4	Pass	238	9	148	* For use in automotive disc, drum and anti-skid brake systems and clutch systems.
DOT 4	1250	2.1	Pass	270	8	170	* For hydraulic disc brakes and drum brakes on motorcycles, cars, commercial vehicles and machines.

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

MACHINE OILS

زيوت الآلات

API Viscosity	Specific gravity (15/4 °C)	K. Viscosity (cSt)		VI	Flash Point °C	Pour Point °C	copper corrosion (100°C, 3hrs)	Application
		40°C	100°C					
ISO VG 10	0.830	10.0	2.7	108	179	-45	1a	*High speed spindle bearing
ISO VG 15	0.830	15.0	3.5	112	208	-39	1a	
ISO VG 22	0.842	22.0	4.37	107	224	-27	1a	
ISO VG 68	0.870	68.0	8.92	105	240	-24	1a	*Multi-purpose industrial oil
ISO VG 100	0.878	100.0	11.7	105	248	-21	1a	
ISO VG 150	0.880	150.0	15.2	102	252	-12	1a	
ISO VG 220	0.885	220.0	19.5	101	256	-12	1a	
ISO VG 320	0.890	320.0	25	100	260	-9	1a	
ISO VG 460	0.890	460.0	30.9	97	266	-9	1a	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



AVAILABLE PACKING

20L, 208L



AVAILABLE PACKING
1L, 4L, 5L, 20L, 208L

INDUSTRIAL GEAR OILS

زيوت التروس الصناعية

ISO Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 68	0.870	68.0	8.8	102.0	242	-27	1b	*Multi-purpose EP industrial oil
ISO VG 100	0.880	100.0	11.5	102.0	248	-27	1b	
ISO VG 150	0.880	150.0	15.1	101.0	252	-27	1b	
ISO VG 220	0.890	220.0	19.5	101.0	256	-24	1b	
ISO VG 320	0.895	320.0	24.9	100.0	270	-24	1b	
ISO VG 460	0.901	460.0	31.7	100.0	276	-21	1b	
ISO VG 680	0.901	680.0	43.0	106.0	282	-21	1b	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

HEAT TRANSFER OIL

زيت نقل الحرارة

API Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 32	0.850	32.0	5.5	108	230	-15	1a	*Various kinds of oil application for heat transfer
ISO VG 46	0.860	46.0	7.0	109	250	-15	1a	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

TRANSFORMER OIL

زيت المحولات

API Viscosity	K.Viscosity (cSt) 40 °C	Viscosity Index	Flash Point (PMCC)	Pour Point	Before Treatment	After Treatment	Application
Inhibited	8.9	≥110	≥150	-30	>30	>70	*Transformer oil is used to insulate high-voltage electrical infrastructure such as transformers, capacitors, switches and circuit breakers.
Uninhibited I	15.0	≥110	≥150	-36	>30	>70	
Uninhibited II	10.0	≥110	≥150	-48	>30	>70	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



AVAILABLE PACKING
20L, 208L

MARINE ENGINE OIL / SLIDEWAY OILS



MARINE ENGINE OIL

زيت المحرك البحري

API Viscosity	K.Viscosity(cSt)	VI	TBN	Flash Point °C	Pour Point °C	Application
	100 °C					
SAE 30	9.3	≥95	40	≥230	-12	* All types of marine engines
SAE 40	12.5	≥95	40	≥230	-9	
SAE 50	16.3	≥95	40	≥230	-6	

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

SOLUBLE CUTTING OIL

زيوت القطع القابلة للذوبان

Cutting Oil	Specific gravity (15/4 °C)	K.Viscosity(cSt)		Emulsion Type	Corrosion Test	pH at 3% Emulsion	Refractometer correction Factor	Application
		40 °C	100 °C					
Soluble Cutting Oil	0.95	>40.0	>6.0	Milky	3	9.1	1	*fabricating, forming, stamping, turning, milling sawing, bending, broaching and tapping.

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

THREAD CUTTING OIL

زيت قطع الخيط

Cutting Oil	K.Viscosity(cSt)	Copper Strip Corrosion for 3 Hrs.	Flash Point	Active Sulphur	Application
	40 °C				
Thread Cutting Oil	32	1a	>215	Nil	*lubricate, dissipate heat, from the tool and workpiece, and remove chips during the cutting process.

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

NEAT CUTTING OIL

زيت قطع المنظم

Cutting Oil	K.Viscosity(cSt)	Copper Strip Corrosion for 3 Hrs.	Flash Point	Active Sulphur	Application
	40 °C				
Neat Cutting Oil	36	1a	>215	Nil	* light machining to heavy-duty operations, eg., gear hobbing, broaching, turning, honing and drilling.

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

SLIDEWAY OILS

زيوت الممرات المنزلقة

API Viscosity	Specific gravity (15/4 °C)	K.Viscosity(cSt)		VI	Flash Point °C	Pour Point °C	copper-corrosion (100°C, 3hrs)	Application
		40 °C	100 °C					
ISO VG 32	0.860	32.0	5.9	130	230	-36	1a	*Slideway and hydraulic oil for lightly loaded machining equipments
ISO VG 68	0.874	68.0	9.7	124	248	-27	1a	*Slideway for medium and heavy loaded equipments
ISO VG 100	0.885	220.0	20.5	248	252	-24	1a	*Vertical or heavily loaded slideway oil

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L



AVAILABLE PACKING

1L, 4L, 5L, 20L, 208L

MULTI-PURPOSE GREASE

شحم متعدد الأغراض



Color	Soap	Penetration (NLGI)	Dropping Point (°C)	Water Washout (%wt)	Copper Corrosion	Service Temp	Properties	Application
VIRGO EP GREASE – LITHIUM BASE								
Pale Yellow	Lithium	00 (400-430)	190	< 5	PASS	-20 ~ 130°C	*Extreme pressure (lead-free EP) *Oxidation & corrosion inhibitors *Resists water wash-out *DIN 51502 KP1K–KP4K	*Plain & anti-friction bearings *Wheel bearings, linkages *Centralized lubrication *Marine, mining & industrial machinery
		0 (355-385)						
		1 (310-340)						
		2 (265-295)						
		3 (220-250)						
VIRGO MP GREASE – LITHIUM BASE								
Pale Yellow	Lithium	00 (400-430)	180-190	< 5	PASS	up to 180°C short term	*Lithium hydroxy stearate *Oxidation & corrosion inhibitors *Good structure stability	*Automotive grease points *Plain & rolling bearings *Electric motors, machine tools *Textile, paper & construction equipment
		0 (355-385)						
		1 (310-340)						
		2 (265-295)						
		3 (220-250)						
VIRGO MP GREASE – CALCIUM BASE								
Pale Yellow	Calcium	2 (265-295)	130-144	< 5	PASS	–	*Water resistant *Tackiness & EP agents	*Vehicle chassis *Trucks, off-highway & construction
		3 (220-250)						
LITHIUM GREASES – COLOURED								
Red	Lithium	2 (270)	210	–	PASS	-30.0 ~ 140°C	*Excellent coherence	*Noise-reducing, water-resisting lubrication areas *Rolling or sliding bearings requiring sealing
Blue		2 (270)	210	–	PASS	-30.0 ~ 140°C		
Black	Lithium	2 (270)	220	–	PASS	-30.0 ~ 150°C	*Very high EP *Anti-wear *Usable under severely high load	*Automotive CVJ *Anti-wear for various bearings *Joint and spline shaft

*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

AVAILABLE PACKING

0.5Kg, 1Kg, 15Kg, 180Kg

SPECIAL GREASES

شحوم خاصة

High-speed, Hi-temp & Heavy Load Grease

Color	Soap	Penetration (NLGL)	Melting Point (°C)	Copper Corrosion	Service Temp	Properties	Application
Gray black	Inorganic	2	NONE	PASS	-40.0°C ~280°C	*Not carbonized at high temp *Tenacious lubrication	*Fan, coating roll, furnace, heat blower, tender, klin, painting line trolley, C&L calendar machine & etc...
Black	Inorganic	2	NONE	PASS	-45.0°C ~290°C	*Long life under hi-temp *Keep lubricating under hot steam	



Synthetic Grease Lithium-Complex Base

Color	Texture	Dropping Point	Water Washout Resistance	Copper Corrosion	Worked Penetration	NLGI Classification	Application
Red	Smooth	265	6	PASS	265-295	1-2	*Operating under high loads and temperatures, heavy machinery, couplings and transmission shafts.

Lithium - Complex Grease

Color	Texture	Dropping Point	Water Washout Resistance	Copper Corrosion	Worked Penetration	NLGI Classification	Application
Red	Smooth	265	6	PASS	265-295	1-2	Automotive, agricultural, construction, industry, mining, paper and steel mills.



Calcium Sulfonate Grease

Color	Texture	Dropping Point	Water Washout Resistance	Copper Corrosion	Worked Penetration	NLGI Classification	Application
Pale Yellow	Smooth	90 -110	<5	PASS	265-295	1-2	Automotive, agricultural, construction, industry, mining, paper and steel mills.

High Speed Synthetic Grease

Color	Soap	Penetration (NLGL)	Melting Point (°C)	Copper Corrosion	Service Temp	Properties	Application
White	Lithium	2	200	PASS	-40.0°C ~130°C	*No splash at high speed *Low temp characteristics *Compatible with plastics	*Textile machine, machine tool spindle, optical machine, precision machine & etc...
White	Lithium	2	200	PASS	-50.0°C ~140°C		



AVAILABLE PACKING
0.5Kg, 1Kg, 15Kg, 180Kg



Table of Contents

جدول المحتويات

- | | |
|---------------------------------|--|
| ▶ GASOLINE / DIESEL ENGINE OILS | زيتو محركات البنزين والديزل |
| ▶ GEAR & ATF LUBRICANTS | زيتو التروس والسائل ناقل الحركة الأوتوماتيكي |
| ▶ MOTORCYCLES LUBRICANTS | زيتو تشحيم الدراجات النارية |
| ▶ HYDRAULIC OILS / MACHINE OILS | الزيتو الهيدروليكية / زيتو الآلات |
| ▶ INDUSTRIALS LUBRICANTS | زيتو التشحيم الصناعية |
| ▶ MARINE LUBRICANTS | زيتو التشحيم البحرية |
| ▶ MULTI-PURPOSE GREASES | شحمة متعدد الأغراض |
| ▶ SPECIALITY LUBRICANTS | الشحوم الخاصة |



AUTOMOTIVE



MOTORCYCLE



TRANSPORT



MINING



MARINE



AGRICULTURE



INDUSTRIAL



FORESTRY

POWERING A **SMOOTHER** TOMORROW



MAKING THE RIGHT CHOICE

'GOOD' engine oils are conventional mineral based engine oils suitable for the everyday driver. Standard service conditions specified in the owner's manual can be met with this range of products.

'BETTER' engine oils are synthetic blends. They provide more protection than conventional or 'good' grades. These oils are suitable for severe service conditions where a vehicle may endure stop-start driving or short trips, long idling periods, towing of heavy loads (such as boats, trailers or driving a utility) or may require long drain capabilities.

'BEST' engine oils are full synthetic grades that offer superior protection. Severe and high performance applications can be met with this range. If you want the ultimate protection for your engine, Virgo recommends the use of fully synthetic lubricants.

POWERING A **SMOOTHER** TOMORROW







HEAD OFFICE

VIRGO LUBRICANTS TRADING L.L.C

☎ Mobile : +971 52 452 6277

✉ Email : virgolubes@gmail.com

POWERING A SMOOTHER TOMORROW

☎ +971 52 452 6277

✉ virgolubes@gmail.com